

ADA COMPLIANCE CHECKLIST (RESTAURANT)

Meet
Fail
N/A

Parking Lot

- | | | | |
|--------------------------|--------------------------|--------------------------|---|
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Tow away warning at entrance to lot |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Accessible spaces - minimum 1, and at least 1 for each 25 spaces (e.g., 26 spaces requires 2 accessible spaces) |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Accessible spaces at least 96 in. wide |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | At least 1 Van Accessible space (96 in. wide, adjacent to 96 in. wide access aisle) |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Signage at Accessible spaces (Handicapped Parking sign at each space; Van Accessible sign below it at the Van space). |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Access Aisle (shortest possible route between accessible spaces and entrance) |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Minimum 36 in. wide (96 in. wide adjacent to van space) |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Maximum slope 1/20, maximum cross slope 1/50 |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Curb cut (not ramp) where aisle intersects curb (e.g., any step over 1/2 in.) |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Bevel at any change in level between 1/4 in. and 1/2 in. |

Curb Cut

- | | | | |
|--------------------------|--------------------------|--------------------------|---|
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Maximum slope 1/12 |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Minimum width 48 in. |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | If in sidewalk, sides must be sloped, not curb. Maximum slope 1/10. |

Doors

- | | | | |
|--------------------------|--------------------------|--------------------------|--|
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | 32 in. minimum width of clear space (measured from frame to open door) |
| <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> | Maximum threshold height 1/2 in. (beveled) |

Meet	Fail	N/A	
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Accessible hardware (e.g., does not require tight gripping, pinching or twisting)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Hardware maximum height 48 in.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Opening force - exterior: maximum 5 lbs
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	- interior: maximum 5 lbs.
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	If 2 doors in line: - both swing same direction, or away from each other
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	- minimum space between doors 48 in. plus width of any door which swings into the space
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Door closer (must take at least 3 seconds to go from open (70°) to 3 in. from closed)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Minimum 60 in. X 60 in. level clear space in front of door (pull side)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Minimum 48 in. X 48 in. level clear space in front of door (push side)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Minimum 18 in. clear space between strike side edge of door and any obstruction
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Kick plate (lowest 10 in. of door is smooth, uninterrupted surface)

Bathroom

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Door meets all applicable criteria for interior door (above)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Braille sign on strike side jamb (mounted at 60 in. on center)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Pictogram (circle for girl, triangle for boy) on door (mounted at 60 in. on center)

Sink/counter

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Accessible hardware (lever, push or automatic - minimum 10 second run)
--------------------------	--------------------------	--------------------------	--

Meet
Fail
N/A

- Minimum approach clear space 30 in. X 48 in.
- Counter not more than 34 in. from floor
- Exposed pipes insulated, no sharp corners or edges
- Knee space - first 8 horizontal inches, minimum 29 in. vertical clearance
- beyond 8 horizontal inches, minimum 27 in. vertical clearance

Urinals

- Rim maximum 17 in. from floor, maximum 12 in. from back wall
- Approach clear space minimum 48 in. X 30 in.
- Privacy shields - minimum 29 in. between
- cannot extend beyond urinal
- Flush maximum 44 in. from floor (or automatic)

Toilets/stalls

Toilet

- Seat height between 17 in. and 19 in.
- Centerline of toilet exactly 18 in. from side wall (near side)
- Minimum 32 in. clear space between toilet and far side wall
- Flush control maximum 40 in. from floor, on side of far wall
- Front of toilet at least 48 in. from door (if door opposite); at least 60 in. from front wall if door in side wall

Stalls

- Door meets all applicable criteria for interior door (above)
- Minimum 59 in. deep, 60 in. wide
- Continuous paper dispenser within reach from toilet, minimum 19

Meet
Fail
N/A

- in. from floor
- 2 grab bars - on back wall at least 36 in. long
- on near side wall, at least 54 in. long, beginning not more than 12 in. from back wall
- Grab bars exactly 33 in. from floor, 1 1/2 in. from wall
- Grab bar diameter between 1 1/4 in. and 1 1/2 in.

Miscellaneous

- Operable element of all dispensers maximum 40 in. from floor
- Mirrors, bottom maximum 40 in. from floor

Dining/service Area

Tables

- At least 1, and not less than 5% of tables are accessible
- Built in tables, top 34 in. from floor
- Seating clear space at least 30 in. wide, 48 in. deep (up to 19 in. of depth can be under table)

Operable equipment (e.g., drink machine)

- Highest operable part maximum 48 in., minimum 15 in. from floor
- No need to reach more than 20 in. to use
- Clear space to approach at least 48 in. X 30 in.

Eating counter

- Minimum 5 foot section between 28 in. and 34 in. from floor, or accessible tables available in same area

Meet
Fail
N/A

Service counter

Minimum 36 in. long section between 28 in. and 34 in. from floor